

MODULES

Manual Call Points

W5A-RP06SG-K013-41



Includes transparent cover PS200 and surface mounting enclosure IP67.

Manual Call Point isolated IP67

The IP67 Honeywell Morley-IAS addressable call point is used in humidity environments to provide a safe and reliable device in areas with dust or humidity. The IP67 addressable MCP is provided with IP67 surface mounting enclosure and transparent cover.

TECHNICAL DATA

OPERATING VOLTAGE	15 ... 30 V DC
QUIESCENT CURRENT	260 uA @ 24 V DC (w/o isolator) 360 uA @ 24 V DC (with isolator)
ALARM CURRENT	6 mA @ 24 V DC
TEMPERATURE RANGE	-30°C ... 70°C
RELATIVE HUMIDITY	0 ... 95% (non-condensing)
DIMENSION	H: 97.5 mm W: 105 mm D: 75.5 (surface mounted & transparent cover)
WEIGHT	350g
INGRESS PROTECTION	IP67
MAXIMUM WIRE GAUGE	2.5 sqmm
MATERIAL	ABS plastic
COLOR	red

PS031W




Surface mounting base red for MCP

Surface mounting box for M5A addressable MCP red.

TECHNICAL DATA

DIMENSION	H: 87 mm W: 93 mm D: 32 mm
-----------	----------------------------

MUS156



10 pieces

Spare EN54-11 glass pack for MCP

10 Spare breakable glass pack for Honeywell Morley-IAS addressable manual call points.