



A Tco International Company

PG934P/PI/P934P/PI/P934P/PI

PowerG (PI) PowerG (PI) Pir/Immune Motion Detector with Integrated Camera Installation Instructions

Contents

1. Wireless pet immune motion detector with camera
1. Manual
1. Hardware pack (2 screws/piles)
1. 3V Lithium CR-123A battery pack with connector

Overview

The PG934P/PI/P934P/PI/P934P/PI are 2-way wireless digital PIR/PIR immune motion detectors with integrated cameras and microphones for home use. The PG934P Series distinguishes between human beings and pets weighing up to 38 kg (85 lb). Target Specific Imaging™ and reduces false alarm by using True Motion Recognition™. Built-in link quality indicators reduce installation time by eliminating the need for the installer to physically approach the control panel.

Camera Features

- Color or black & white images
- Auto-setup for brightness and contrast via the control panel
- Day and night CMOS camera, with IR illumination. This allows taking pictures in full darkness.
- Camera range of 12m (40ft) with IR illumination (1m (3ft))
- Camera operation modes
- Post alarm - pictures are taken after detection by detector.
- Optical audio with images
- Video Verification

1. The camera and the listen-in feature are not to be enabled in UL listed product.
2. The microphone is not to be enabled in a UL listed product.

Please be advised that this product may record and transmit photographs, images and audio recordings in the event of an alarm condition, and that such images and recordings may be activated remotely by a monitoring company or other third party with authorized access to the system to which this device is connected. It is the responsibility of the party installing and/or monitoring the product, and of the end user, to ensure that the installation, configuration and use of the product complies with applicable laws, including, without limitation, laws related to privacy, end user notification and/or consent, posting of signage, and registration of the application/firmware with local privacy authorities. The manufacturer disclaims, and shall be held harmless and indemnified by the purchaser of this product, for any and all liability related to compliance with such applicable laws by the installing party, monitoring company or any third party user of the product. The product may be configured to limit the conditions under which the device will record, transmit or permit remote access to such photographic images and audio recordings.

Device Setup

Observe polarity when installing battery. Dispose of used batteries according to the manufacturer's instructions and according to local regulations. Batteries are to be replaced by service persons only. Do not attempt to replace batteries yourself. Do not attempt to be installed by service persons in non-hazardous locations only.

Legend

- A. Microphone
- B. Camera lens
- C. IR LED
- D. Light Sensor
- E. Battery connector
- F. Horizontal view
- G. Vertical view
- H. Sound bracket Knockout
- I. Mounting bracket
- J. Mounting Knockout (for surface mounting)
- K. Break-away base segment (shaded)
- L. Mounting bracket Knockout
- M. Mounting Knockout (3 of 6 - for corner mounting)

Installing Battery

1. Release screw and remove cover.
2. Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.

Release screw and remove cover.

Remove cover from base.



