

# HID® Prox 125 kHz Proximity – Readers



	ProxPoint Plus®	MiniProx®	Thinline® II	ProxPro®	ProxPro® II	ProxPro® with Keypad	EntryProx™	MaxiProx®	Prox80™
<b>Base Model Number</b>	6005B/6008B	5365E/5368E	5395C/5398C	5355A/5352A/ 5358A	5455B/ 5458B	5355A/5352A/ 5358A	4045C	5375A	5405A/5408A
<b>Dimensions</b>	3.13" x 1.7" x 0.66" (8.0 cm x 4.5 cm x 1.5 cm)	6.0" x 1.7" x 1.0" (15.0 cm x 4.5 cm x 2.0 cm)	4.7" x 3.0" x .68" (12.0 cm x 7.5 cm x 1.5 cm)	5.0" x 5.0" x 1.0" (12.5 cm x 12.5 cm x 2.5 cm)			5.25" x 2.75" x 1.37" (13.5 cm x 7.0 cm x 3.5 cm)	12.0" x 12.0" x 1.0" (30.5 cm x 30.5 cm x 2.5 cm)	3.15" x 3.15" x 0.8" (8.0 cm x 8.0 cm x 2.0 cm)
<b>Weight</b>	3.6 oz (102 g)	7.89 oz (224 g)	7.33 oz (208 g)	9.62 oz (273 g)	13.65 oz (387 g)	9.62 oz (273 g)	11.76 oz (333 g)	50.8 oz (1440 g)	2.2 oz (63 g)
<b>Read Range</b>	Up to 3.0" (7.5 cm)	Up to 5.5" (14.0 cm)		Up to 8.0" (20.5 cm)			Up to 3.0" (7.5 cm)	Up to 24.0" (61.0 cm)	Up to 5.5" (14.0 cm)
<b>Mounting</b>	Mullion		Single-gang electrical box	Single-gang electrical box; Glass Mount Kit Available			US or EU single-gang box, wall surface, or on glass with included adhesive pads	Mount on non-metallic surfaces for optimal read range performance.	EU/Asian single-gang box
<b>Power Supply</b>	5-16 VDC			10-28.5 VDC	5-16 VDC	10-28.5 VDC	10-15 VDC	12 VDC or 24 VDC	5-16 VDC
<b>Current Requirements</b>	35 mA			155 mA	40 mA	155 mA	150 mA	200/700 mA @ 12 VDC 260 mA/1.2 A @ 24 VDC	35 mA
<b>Termination</b>	Pigtail	Pigtail or Terminal Strip	Pigtail			Terminal Strip			Pigtail
<b>Output Formats</b>	Wiegand or Clock-and-Data			Wiegand, Clock-and-Data, RS-232 or RS-422	Wiegand or Clock-and-Data	Wiegand, Clock-and-Data, RS-232 or RS-422	Wiegand	Wiegand, Clock-and-Data, RS-232, RS-422 and RS-485	Wiegand or Clock-and-Data
<b>Tamper</b>	No			Switch	No	Switch		Switch	No
<b>Indoor/Outdoor</b>	Both								
<b>Warranty</b>	Lifetime								

HID Prox