

DHL24-F600

24" FHD LCD Monitor



Features :

- Industrial level IPS LCD panel, suitable for extensive 7×24 continuous works
- High fidelity digital processing, brilliant and vivid video
- 5ms fast response time, no image ghosting
- Built-in speaker
- Ultra-narrow bezel design with 178°/178° wide viewing angle make your vision more open



Technical Specification

Model

| | |
|-------|------------|
| Model | DHL24-F600 |
|-------|------------|

System

| | |
|---------------------------------|--------------------------------|
| Diagonal | 23.8"(16:9) |
| Resolution | 1920×1080 |
| LCD Technology | IPS |
| Backlight | LED |
| Brightness/Luminance (Standard) | 230 cd/㎡ |
| Contrast | 1000:1 |
| Angle of View | 178°/178°(vertical/horizontal) |
| Response Time | 5ms |
| Display Color | 16.7M |
| Hanging Hole Size | 100×75 mm |

Signals

| | | |
|--------|----------|-------------------------------|
| Input | Standard | HDMI×1, VGA(D-Sub)×1, Audio×1 |
| | Optional | - |
| Output | Standard | Speaker×1 |
| | Optional | - |

General

| | |
|------------------------|-----|
| Consumption (Standard) | 36W |
|------------------------|-----|

| | |
|-----------------------|-------------------------------|
| Consumption (Standby) | ≤0.5W |
| Power Supply | AC100~240V (+/-10%), 50/60 Hz |
| Net Weight | 3.0kg |
| Dimensions (no base) | 542.0×322.5×40.3mm |
| Work Environment | Temperature: 0 C ~50 C |
| | Humidity: 20%~90% |

Accessory

| | |
|----------|-----------------------------------|
| Standard | HDMI cable, power cable, pedestal |
| Optional | Hanging bracket |

Dimensions(mm)

